


## **DTB35-10**

Terminal Type - DTB35-10, Hybrid Distribution Blocks, nominal voltage: 800 V, nominal current: 125 A, Rated cross-section -IC -35 mm<sup>2</sup>, OG - 10 mm<sup>2</sup>, connection method: Spring clamp connection, number of connections: 4, cross-section: 10 mm<sup>2</sup> - 50 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, colour: GREY



### Approvals

CE

### General Information

Product Name	DTB35-10
Connection Method	Spring Cage Connection
Rating	800 V/125 A/IC -35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup> /NAV Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M8

### Dimensions & Weight

Width	17.5 mm	0.69 inch
Length	89 mm	3.5 inch
Height	39.75 mm	1.56 inch
Weight of std. Packing Unit	2.94 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	IC- 6 mm <sup>2</sup> , OG - 1.5 mm <sup>2</sup>
Conductor cross section flexible max	IC- 35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup>
Conductor cross section solid min	IC- 6 mm <sup>2</sup> , OG - 1.5 mm <sup>2</sup>
Conductor cross section solid max	IC- 35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	800 V
Nominal Current $I_n$	125 A
Nominal cross section	IC -35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup>
Short-time current	4.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

