



## DTB35-10X4

Terminal Type - DTB35-10X4 , Hybrid Distribution Blocks, nominal voltage: 1000 V, nominal current: 125 A, Rated cross-section -IC -35 mm<sup>2</sup>, OG - 10 mm<sup>2</sup> ,connection method: Spring clamp connection, number of connections: 5, cross-section: 10 mm<sup>2</sup> - 50 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals

CE

### General Information

Product Name	DTB35-10X4
Connection Method	Spring Cage Connection
Rating	1000 V/125 A/IC-35 mm <sup>2</sup> , OG-10 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	16.2 mm	0.64 inch
Length	86 mm	3.39 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	2.54 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	IC- 6 mm <sup>2</sup> , OG - 1.5 mm <sup>2</sup>
Conductor cross section flexible max	IC- 35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup>
Conductor cross section solid min	IC- 6 mm <sup>2</sup> , OG - 1.5 mm <sup>2</sup>
Conductor cross section solid max	IC- 35 mm <sup>2</sup> , OG - 10 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	125 A
Nominal cross section	IC-35 mm <sup>2</sup> , OG-10 mm <sup>2</sup>
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

