


ETDD4N

Terminal Type - ETDD4N , Multi level Ground terminal block for photo voltaic applications , connection method: Screw connection, Rated cross section: 4.0 mm², number of connections: 4, cross-section: 0.5 mm² - 4 mm² ,, mounting type: TS 35/7.5 , TS 35/15



Approvals

CE

General Information

Product Name	ETDD4N
Connection Method	Screw Connection
Rating	NAP V/NAP A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	62.5 mm	2.46 inch
Height	65.5 mm	2.58 inch
Weight of std. Packing Unit	1.9 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	4 mm ²
Short-time current	NAP kA
Rated surge voltage	NAP kV
Degree of pollution	3

