



KUDD4CA1

Terminal Type - KUDD4CA1 , Component Housings terminal block (Two Diode with Common Anode configuration , nominal voltage: 500 V, Diode : 1N 4007 , Diode current : 1 A , Diode Reverse Voltage - 1000 V, Rated cross-section: 2.5 mm² , connection method: Screw connection, number of connections: 3, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CE

General Information

Product Name	KUDD4CA1
Connection Method	Screw Connection
Rating	500 V/Diode Current - 1 A/2.5 mm ² /0.4 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	54 mm	2.13 inch
Height	59.2 mm	2.33 inch
Weight of std. Packing Unit	1.38 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Black , Green , Khakhi , Gray ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	Diode Current - 1 A
Nominal cross section	2.5 mm ²
Short-time current	NAP kA
Rated surge voltage	6 kV
Degree of pollution	3

