



KUDD4CC2

Terminal Type - KUDD4CC2 , Component Housings terminal block, nominal voltage: 500 V, Diode : 1N 4007 , Common Cathode , Diode current: 1 A , Diode Reverse Voltage - 1000 V, Rated cross-section - 2.5 mm², connection method: Screw connection, number of connections: 3, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals

CE

General Information

| | |
|-----------------------------|---|
| Product Name | KUDD4CC2 |
| Connection Method | Screw Connection |
| Rating | 500 V/Diode Current - 1 A/2.5 mm ² /0.4 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 100 |
| Country Of Origin | India |
| Screw thread | M3 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 6 mm | 0.24 inch |
| Length | 54 mm | 2.13 inch |
| Height | 59.2 mm | 2.33 inch |
| Weight of std. Packing Unit | 1.38 Kg | |

Material Data

| | |
|---------------------|---|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , Gray , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 2.5 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 2.5 mm ² |

Ratings - IEC

| | |
|----------------------------------|---------------------|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 500 V |
| Nominal Current I_n | Diode Current - 1 A |
| Nominal cross section | 2.5 mm ² |
| Short-time current | NAV kA |
| Rated surge voltage | 6 kV |
| Degree of pollution | 3 |

