



KUDDF4AD24V

Terminal Type - KUDDF4AD24V, Fuse terminal block with LED of 24 V for fuse failure indication, nominal voltage: 24 V, nominal current: UT-6.3 A / LT 28 A, suitable size of cartridge fuse: 5X20 mm and 5x25 mm, connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5 , TS 35/15 , TS 32



Approvals

CE

General Information

Product Name	KUDDF4AD24V
Connection Method	Screw Connection
Rating	24 V/UT-6.3 A , LT-28 A/2.5 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	8 mm	0.31 inch
Length	74 mm	2.91 inch
Height	58.6 mm	2.31 inch
Weight of std. Packing Unit	1.28 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	24 V
Nominal Current I_n	UT-6.3 A , LT-28 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

