



KUDT4-2X2

Terminal Type - KUDT4-2X2, Knife disconnect terminal block, nominal voltage: 800 V, nominal current: 20 A, Rated cross-section: 4.0 mm², connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15



Approvals

CE

General Information

Product Name	KUDT4-2X2
Connection Method	Screw Connection
Rating	800 V/20 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	67 mm	2.64 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	1.85 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC-60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	20 A
Nominal cross section	4 mm ²
Short-time current	0.48 kA
Rated surge voltage	8 kV
Degree of pollution	3

