



## **KUFH4D1**

Terminal Type - KUFH4D1, Fuse terminal block with LED for 24 VDC, nominal voltage: 24 V, nominal current: 12 A, Rated cross-section - 4 mm<sup>2</sup>, suitable size of cartridge fuse: 6.35X32 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals

CE

### General Information

Product Name	KUFH4D1
Connection Method	Screw Connection
Rating	24 V/12 A/4 mm <sup>2</sup> /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	9 mm	0.35 inch
Length	76.5 mm	3.01 inch
Height	53.5 mm	2.11 inch
Weight of std. Packing Unit	1.9 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC-60947-7-3
Nominal Voltage $U_n$	24 V
Nominal Current $I_n$	12 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

