


KUPDS6

Terminal Type - KUPDS6, Test Disconnect Terminal Block, nominal voltage: 500 V, nominal current: 32 A, Rated cross-section: 6.0 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CE

General Information

Product Name	KUPDS6
Connection Method	Screw Connection
Rating	500 V/32 A/6 mm ² /0.8 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	57 mm	2.24 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	2.55 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	32 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

