


## KUPTD6

Terminal Type - KUPTD6 , Test Disconnect Terminal Block , nominal voltage: 630 V, nominal current: 24 A, connection method: Screw connection, number of connections: 2, Rated cross-section: 6.0 mm<sup>2</sup> , cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals

CE

### General Information

|                             |                                      |
|-----------------------------|--------------------------------------|
| Product Name                | KUPTD6                               |
| Connection Method           | Screw Connection                     |
| Rating                      | 630 V/24 A/6 mm <sup>2</sup> /1.5 Nm |
| HSN Number                  | 85389000                             |
| Standard Packing Qty(in No) | 50                                   |
| Country Of Origin           | India                                |
| Screw thread                | M3.5                                 |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 8 mm    | 0.31 inch |
| Length                      | 72.5 mm | 2.85 inch |
| Height                      | 72.5 mm | 2.85 inch |
| Weight of std. Packing Unit | 1.7 Kg  |           |

### Material Data

|                     |  |
|---------------------|--|
| Insulating Material | Polyamide 6,6                                  |
| Standard Colour     | Gray   |
| Colour Variants     | Red , Yellow , Blue , Black , Green , Khakhi , |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm <sup>2</sup> |
| Conductor cross section flexible max | 6 mm <sup>2</sup>   |
| Conductor cross section solid min    | 0.5 mm <sup>2</sup> |
| Conductor cross section solid max    | 10 mm <sup>2</sup>  |

**Ratings - IEC**

|                                  |                   |
|----------------------------------|-------------------|
| Connection in acc. with standard | IEC 60947-7-1     |
| Nominal Voltage $U_n$            | 630 V             |
| Nominal Current $I_n$            | 24 A              |
| Nominal cross section            | 6 mm <sup>2</sup> |
| Short-time current               | 0.72 kA           |
| Rated surge voltage              | 8 kV              |
| Degree of pollution              | 3                 |

