


KUTD10NV

Terminal Type - KUTD10NV , Disconnecting terminal block, nominal voltage: 800 V, nominal current: 61 A, Rated cross-section- 10 mm², connection method: Screw connection, number of connections: 2, cross section: 1.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals

CE

General Information

Product Name	KUTD10NV
Connection Method	Screw Connection
Rating	800 V/61 A/10 mm ² /1.2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	8 mm	0.31 inch
Length	61 mm	2.4 inch
Height	57.5 mm	2.26 inch
Weight of std. Packing Unit	1.56 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	61 A
Nominal cross section	10 mm ²
Short-time current	1.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

