


## OAT6DTS

Terminal Type - OAT6DTS, Test Disconnect Terminal Block, nominal voltage: 1000 V (Tested at 1100 V), nominal current: 41 A, connection method: Bolt connection, number of connections: 2, cross-section: 0.5 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15, TS 32



### Approvals

CE

### General Information

Product Name	OAT6DTS
Connection Method	Bolt Connection
Rating	1000 V/41 A/6 mm <sup>2</sup> /1.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	40
Country Of Origin	India
Screw thread	M4

### Dimensions & Weight

Width	11 mm	0.43 inch
Length	83 mm	3.27 inch
Height	52 mm	2.05 inch
Weight of std. Packing Unit	1.6 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	6 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	41 A
Nominal cross section	6 mm <sup>2</sup>
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

