



SCF6

Terminal Type - SCF6, Fuse Terminal block, nominal voltage: 800 V, nominal current: 10 A , Rated cross-section - 6 mm², suitable size of cartridge fuse: 5X20 mm, connection method: Spring Cage Connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15



Approvals

CE

General Information

Product Name	SCF6
Connection Method	Spring Cage Connection
Rating	800 V/10 A/6 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	13 mm	0.51 inch
Length	62 mm	2.44 inch
Height	60 mm	2.36 inch
Weight of std. Packing Unit	1.46 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC-60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	10 A
Nominal cross section	6 mm ²
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

