



## SGQ10-1X2

Terminal Type - SGQ10-1X2, Multi-Conductor Ground modular terminal block, connection method: Spring Cage connection, number of connections: 3, Rated cross-section: 10 mm<sup>2</sup>, cross-section: 0.2 mm<sup>2</sup> - 16 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15.



### Approvals

CE

### General Information

Product Name	SGQ10-1X2
Connection Method	Spring Cage Connection
Rating	NAP V/NAP A/10 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	10 mm	0.39 inch
Length	99 mm	3.9 inch
Height	48 mm	1.89 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	10 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	16 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage $U_n$	NAP V
Nominal Current $I_n$	NAP A
Nominal cross section	10 mm <sup>2</sup>
Short-time current	1.2 kA
Rated surge voltage	0 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage $U_n$	V
ATEX Nominal Current $I_n$	A
ATEX Cross Sec. Flexible Max.	mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	V
B - CSA Nominal Current $I_N$	A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	6 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	V
B - UL Nominal Current $I_N$	A
B - UL Wire Min	24 AWG
B - UL Wire Max	6 AWG