



## SGQ4

Terminal Type - SGQ4 , Ground modular terminal block, connection method: Spring Cage connection, number of connections: 2, cross-section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup>, Rated cross-section - 4 mm<sup>2</sup>, AWG: 24-10, mounting type: TS 35/7.5, TS 35/15



### Approvals



### General Information

Product Name	SGQ4
Connection Method	Spring Cage Connection
Rating	NAP V/NAP A/4 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	56.2 mm	2.21 inch
Height	36 mm	1.42 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

### Rated Conductor Size

Conductor cross section flexible min	0.08 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	6 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage $U_n$	NAP V
Nominal Current $I_n$	NAP A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.48 kA
Rated surge voltage	NAP kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage $U_n$	0 V
ATEX Nominal Current $I_n$	A
ATEX Cross Sec. Flexible Max.	mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	0 V
B - CSA Nominal Current $I_N$	0 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	10 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	0 V
B - UL Nominal Current $I_N$	0 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG