


SPT150

Terminal Type - SPT150, High current connectors with secured hinged cover, nominal voltage: 1000 V, Rated cross-section - 150 mm², nominal current: 320 A, connection method: Bolt connection, number of connections: 2, cross-section: 16 mm² - 150 mm², mounting type: TS 35/7.5, TS 35/15



Approvals

CE

General Information

Product Name	SPT150
Connection Method	Bolt Connection
Rating	1000 V/320 A/150 mm ² /10 Nm
HSN Number	85389000
Standard Packing Qty(in No)	4
Country Of Origin	India
Screw thread	M10

Dimensions & Weight

Width	42 mm	1.65 inch
Length	225.7 mm	8.89 inch
Height	80.3 mm	3.16 inch
Weight of std. Packing Unit	1.43 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	10 mm ²
Conductor cross section flexible max	150 mm ²
Conductor cross section solid min	10 mm ²
Conductor cross section solid max	150 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	320 A
Nominal cross section	150 mm ²
Short-time current	18 kA
Rated surge voltage	8 kV
Degree of pollution	3

