


SPT185

Terminal Type - SPT185 , High current connectors with secured hinged cover, nominal voltage: 1000 V, Rated cross-section - 185 mm², nominal current: 353 A, connection method: Bolt connection, number of connections: 2, cross-section: 25 mm² - 185 mm², mounting type: TS 35/7.5, TS 35/15, colour: GREY



Approvals

CE

General Information

Product Name	SPT185
Connection Method	Bolt Connection
Rating	1000 V/353 A/185 mm ² /14 Nm
HSN Number	85389000
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	55 mm	2.17 inch
Length	286.8 mm	11.29 inch
Height	89.3 mm	3.52 inch
Weight of std. Packing Unit	2.71 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	185 mm ²
Conductor cross section solid min	25 mm ²
Conductor cross section solid max	185 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	353 A
Nominal cross section	185 mm ²
Short-time current	22.2 kA
Rated surge voltage	8 kV
Degree of pollution	3

