



## SQ2.5-3T

Terminal Type - SQ2.5-3T , Multi-tier Feed Through terminal block, connection method: Spring cage connection, nominal voltage : 1000 V , nominal current : Upper Tier - 24 A , Middle Tier - 24 A , Lower Tier - 24 A , Rated cross-section: 2.5 mm<sup>2</sup>, number of connections: 4, cross-section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15



### Approvals

CE

### General Information

Product Name	SQ2.5-3T
Connection Method	Spring Cage Connection
Rating	1000 V/24 A/2.5 mm <sup>2</sup> /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

### Dimensions & Weight

Width	5 mm	0.2 inch
Length	107.6 mm	4.24 inch
Height	58 mm	2.28 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.14 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.08 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

### Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	24 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	6 kV
Degree of pollution	3

### Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage $U_n$	V
ATEX Nominal Current $I_n$	A
ATEX Cross Sec. Flexible Max.	mm <sup>2</sup>

### Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage $U_N$	600 V
B - CSA Nominal Current $I_N$	20 A
B - CSA Wire Min	24 AWG
B - CSA Wire Max	12 AWG

### Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage $U_N$	600 V
B - UL Nominal Current $I_N$	20 A
B - UL Wire Min	24 AWG
B - UL Wire Max	12 AWG